

WR

Wall Mounted Room Thermostats

- Heavy Duty
25 Amps, 120 Vac
22 Amps, 240 Vac
18 Amps, 277 Vac
- Positive Snap-Action Switch
- 3 Degree Control Differential
- UL Listed, CSA Certified



WR-80



WR-90



Description

WR-80
Range 40-80°F Internal Sensing Element
Indicating Thermometer

WR-90
External Sensing Bulb Range 20-90°F


The WR Series Room Thermostats are designed to directly control individual heaters or, by using an external contactor, can control several heaters. The WR-90 is particularly useful for maintaining lower temperatures (in

garages, warehouses, etc.) and avoiding unnecessary heating costs.


Each design has accuracy and provides long reliable service with a 3 degree control differential. Both units are heavy duty, single stage, with a SPST line voltage snap-action switch and are finished with tough, metallic gray enamel housings.

WARNING: Hazard of Fire. The WR thermostats are designed for temperature control service only. Because they do not fail-safe, they should not be used for temperature limiting duty.

Dimensions




Front View




Side View

WR-80



Front View



Side View

WR-90

All Dimensions in Inches (mm)

Specifications and Ordering Information

Model	Temp. Range (°F)	Voltage/Current			Stock	PCN	Wt. (Lbs.)
		120V	240V	277V			
WR-80	40 - 80	25A	22A	18A	S	263177	1
WR-90	20 - 90	25A	22A	18A	S	263185	1

Stock Status: S = stock AS = assembly stock NS = non-stock

Note —

1. Pilot Duty rating, 125 VA for 120 - 277 Vac.